

## ROLF GT 5W-40 SN/CF motor oil

Synthetic

### Description and uses:

State-of-art high-grade all-season easy flowing synthetic motor oil for gasoline and diesel engines including turbocharged engines.

A combination of high-quality base ingredients with cutting-edge additive technology provides a quick and easy engine start at low temperatures, excellent wear protection, and an extended oil change interval. Prevents deposit formation in the oil system, provides the engine cleanliness.

ROLF GT 5W-40 synthetic oil has the highest specification of motor oils for gasoline car engines – API SN.

### Meets:

API SN/CF, ACEA A3/B4-12, MB 229.3, VW 502.00/505.00, RN 0700/0710, Porsche A40, OPEL A/B, JASO MA2

Available package: 1 / 4 / 20 / 208 l

### Typical Analysis:

Properties	Method	Value
SAE (J300)	<b>5W-40</b>	
Oil classification according to API	<b>SN/CF</b>	
Density at 15°C, g/cm <sup>3</sup>	ASTM D 4025	0.857
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	ASTM D 445	14.3
Viscosity index	ASTM D 2270	172
Total Base Number (TBN), mg KOH/g	ASTM D 2896	10.0
Sulphated ash, %	ASTM D 874	1.2
Flash point, °C	ASTM D 92	235
Pour point, °C	ASTM D 97	minus 40



√ Engine protection

√ Fast cold start