

## ROLF JP SAE 0W-20 ILSAC GF-5/API SN motor oil

**Synthetic**

### Description and uses:

ROLF JP SAE 0W-20, ILSAC GF-5/API SN synthetic engine oil is intended for all-season use in gasoline engines where the manufacturers recommend to use engine oils compliant with API SN, ILSAC GF-5 specifications.

Meets the requirements to high-quality engine oils for Japanese, American and Korean cars that require oils to be compliant with highest API and ILSAC categories.

### Meets:

ILSAC GF-5/API SN

**Available package:** 1 / 4 / 20 / 208 l

### Typical Analysis:

Properties	Value
SAE (J300)	<b>0W-20</b>
Oil classification according to API	<b>SN, ILSAC GF-5</b>
Density at 15 °C, kg/m <sup>3</sup>	844
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	8,3
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	42,6
Viscosity index	175
Brookfield dynamic viscosity CCS at - 35 °C, mPas	5500
Total Base Number (TBN), mg KOH/g	6,7
NOACK Volatility, %	13,4
Flash point, °C	223
Pour point, °C	minus 43



✓ **Engine protection**

✓ **Fast cold start**

ROLF Lubricants GMBH  
Gebäude 9115  
Chempark Bayer Leverkusen  
51373 Leverkusen  
Germany

COMMERZBANK  
Neß 7-9  
20457 Hamburg  
IBAN: DE96 2004 0000 0629 5620 00

Tel.: +49 4103 703 68 08,  
+49 0179 7539 329  
e-mail: [info@rolfoil.de](mailto:info@rolfoil.de)  
[www.rolfoil.de](http://www.rolfoil.de)