

ROLF JP SAE 0W-30 ILSAC GF-5/API SN motor oil

Synthetic

Description and uses:

High-quality ROLF JP SAE 0W-30, ILSAC GF-5/API SN engine oil is intended for all-season use in modern gasoline engines where the manufacturers recommend to use engine oils compliant with API SN, ILSAC GF-5 specifications.

Meets the requirements to high-quality engine oils for Japanese, American and Korean cars. Recommended when a vehicle is operated at extremely low ambient temperatures.

Meets:

ILSAC GF-5/API SN

Available package: 1 / 4 / 20 / 208 l

Typical Analysis:

Properties	Value
SAE (J300)	0W-30
Oil classification according to API	SN, ILSAC GF-5
Density at 15 °C, kg/m ³	844
Kinematic viscosity at 100 °C, mm ² /s	11,7
Kinematic viscosity at 40 °C, mm ² /s	64,2
Viscosity index	180
Brookfield dynamic viscosity CCS at - 35 °C, mPas	3500
Total Base Number (TBN), mg KOH/g	6,7
NOACK Volatility, %	13,3
Flash point, °C	223
Pour point, °C	minus 43



✓ **Engine protection**

✓ **Fast cold start**

ROLF Lubricants GmbH
Gebäude 9115
Chempark Bayer Leverkusen
51373 Leverkusen
Germany

COMMERZBANK
Neß 7-9
20457 Hamburg
IBAN: DE96 2004 0000 0629 5620 00

Tel.: +49 4103 703 68 08,
+49 0179 7539 329
e-mail: info@rolfoil.de
www.rolfoil.de