

ROLF JP SAE 10W-30 ILSAC GF-5/API SN motor oil

Synthetic

Description and uses:

ROLF JP SAE 10W-30 ILSAC GF-5/API SN synthetic engine oil is used for greasing modern gasoline engines and those working on gas and gasoline-ethanol blends.

Meets the requirements to highquality engine oils for Japanese, American and Korean cars that require oils to be compliant with highest API categories.

Meets:

ILSAC GF-5/API SN

Available package: 1 / 4 / 20 / 208 l

Typical Analysis:

Properties	Value
SAE (J300)	10W-30
Oil classification according to API	SN, ILSAC GF-5
Density at 15 °C, kg/m ³	861
Kinematic viscositi at 100 °C, mm ² /s	12
Kinematic viscositi at 40 °C, mm ² /s	78,9
Viscosity index	147
Brookfield dynamic viscosity CCS at - 35 °C, mPas	5500
Total Base Number (TBN), mg KOH/g	6,7
NOACK Volatility, %	7,4
Flash point, °C	226
Pour point, °C	minus 33



✓ **Engine protection**

✓ **Fast cold start**

ROLF Lubricants GmbH
Gebäude 9115
Chempark Bayer Leverkusen
51373 Leverkusen
Germany

COMMERZBANK
Neß 7-9
20457 Hamburg
IBAN: DE96 2004 0000 0629 5620 00

Tel.: +49 4103 703 68 08,
+49 0179 7539 329
e-mail: info@rolfoil.de
www.rolfoil.de