

## ROLF JP SAE 5W-20 ILSAC GF-5/API SN motor oil

**Synthetic**

### Description and uses:

ROLF JP SAE 5W-20, ILSAC GF-5/API SN synthetic engine oil is intended for all-season use in gasoline engines where the manufacturers recommend to use engine oils compliant with API SN, ILSAC GF-5 specifications.

A combination of a synthetic base oil and a balanced additives package ensures a quick and easy engine start at low temperatures and an excellent engine greasing from the first seconds of operation.

### Meets:

ILSAC GF-5/API SN

**Available package:** 1 / 4 / 20 / 208 l

### Typical Analysis:

Properties	Value
SAE (J300)	<b>5W-20</b>
Oil classification according to API	<b>SN, ILSAC GF-5</b>
Density at 15 °C, kg/m <sup>3</sup>	849
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	8,8
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	49,7
Viscosity index	157
Brookfield dynamic viscosity CCS at - 35 °C, mPas	4600
Total Base Number (TBN), mg KOH/g	6,7
NOACK Volatility, %	9,3
Flash point, °C	235
Pour point, °C	minus 40



✓ **Engine protection**

✓ **Fast cold start**

ROLF Lubricants GmbH  
Gebäude 9115  
Chempark Bayer Leverkusen  
51373 Leverkusen  
Germany

COMMERZBANK  
Neß 7-9  
20457 Hamburg  
IBAN: DE96 2004 0000 0629 5620 00

Tel.: +49 4103 703 68 08,  
+49 0179 7539 329  
e-mail: [info@rolfoil.de](mailto:info@rolfoil.de)  
[www.rolfoil.de](http://www.rolfoil.de)